

GT



Technical data Luxura GT

Available colours :

Dark Bronze
DecoLight variant:
Blue, Red, Pink, Yellow

Pearl White
DecoLight variant:
Green, Blue, Red, Pink

VIP Gold
DecoLight variant:
Yellow, Blue

Classic Red
DecoLight variant:
White, Blue

Deep Yellow
DecoLight variant:
Blue

• = standard ° = Optional

- The 42 SLi, 42 SLi Int., 42 SLi H. Int., with 1.80 m tubes and shoulder-tanning feature available on request.
- CliMax only available in combination with ContourPlus
- Only available in combination with 1.80 m tubes in the bed.

Type ->	38 SLi	38 SLi Intensive	38 SLi High Intensive	40 SPr	40 SPr Intensive	40 SPr High Intensive	42 SLi	42 SLi Intensive	42 SLi High Intensive	42 SLi IPControl
Surface	Metallic	Metallic	Metallic	Metallic	Metallic	Metallic	Metallic	Metallic	Metallic	Metallic
Inside lighting	•	•	•	•	•	•	•	•	•	•
Tubes top	22 x 100 W	22 x 160 W	22 x 160 W	22 x 120 W	22 x 180 W	22x 180 W	24 x 100 W	24 x 160 W	24 x 160 W	24 x IP tubes 1.80 m
Tubes base	16 x 100 W	16 x 100 W	16 x 160 W	18 x 120 W	18 x 120 W	18 x 180 W	18 x 120 W	18 x 120 W	18 x 180 W	18 x IP tubes 2.00 m
Face tanner	3 x 400 W	3 x 400 W	3 x 400 W	23 x 25 W	23 x 25 W	23 x 25 W	4 x 400 W	4 x 400 W	4 x 400 W	4 x 400 W
Luxura Filter technology	•	•	•	—	—	—	•	•	•	•
HPS	°	°	°	—	—	—	°	°	°	°
2 m tubes in base ¹	—	—	—	•	•	•	•	•	•	•
5 steps adjustable body cooler	•	•	•	•	•	•	•	•	•	•
5 steps adjustable face cooler	•	•	•	•	•	•	•	•	•	•
LED blower decor light	•	•	•	•	•	•	•	•	•	•
Decorative silver panel	•	•	•	•	•	•	•	•	•	•
Loudspeakers (2)	•	•	•	•	•	•	•	•	•	•
SoundAround including My MP3	•	•	•	•	•	•	•	•	•	•
SmartVoice ²		°	°	°	°	°	°	°	°	°
ContourPlus	•	•	•	•	•	•	•	•	•	•
Xsens	°	°	°	°	°	°	°	°	°	°
Qsens	°	°	°	°	°	°	°	°	°	°
CliMax ²	°	°	°	°	°	°	°	°	°	°
BackFlex	•	•	•	° ³	° ³	° ³	° ³	° ³	° ³	° ³
Dust filters	•	•	•	•	•	•	•	•	•	•
EasyLift Acrylic system	•	•	•	•	•	•	•	•	•	•
Sound volume adjustment ²	•	•	•	•	•	•	•	•	•	•
LCD timer display	•	•	•	•	•	•	•	•	•	•
Programmable internal timer	•	•	•	•	•	•	•	•	•	•
Connection for external timer	•	•	•	•	•	•	•	•	•	•
Hour counter	•	•	•	•	•	•	•	•	•	•
2nd hour counter with reset-function	•	•	•	•	•	•	•	•	•	•
Connection	400 V -50 Hz 3~N/PE	400 V -50 Hz 3~N/PE	400 V -50 Hz 3~N/PE	400 V -50 Hz 3~N/PE	400 V -50 Hz 3~N/PE	400 V -50 Hz 3~N/PE	400 V -50 Hz 3~N/PE	400 V -50 Hz 3~N/PE	400 V -50 Hz 3~N/PE	400 V -50 Hz 3~N/PE
Power (with CliMax)	ca. 6,3 (7,1) kW	ca. 7,6 (8,3) kW	ca. 9,3 (10,1) kW	ca. 5,8 (6,6) kW	ca. 7,4 (8,2) kW	ca. 8,5 (9,4) kW	ca. 7,2 (8,0) kW	ca. 9,0 (9,8) kW	ca. 10,2 (10,8) kW	ca. 9,4 (10,4) kW
Fuses	3 x 16 A	3 x 16 A	3 x 16 A	3 x 16 A	3 x 16 A	3 x 20 A	3 x 16 A	3 x 20 A	3 x 20 A	3 x 20 A
Weight (excl. packaging) (CliMax +50kg)	285 kg	305 kg	325 kg	295 kg	315 kg	330 kg	305 kg	325 kg	340 kg	285 kg

