



## Technical data Luxura V<sub>10</sub>

### Available colours:

Royal Red  
Pearl White in de varianten:  
Passion, Romance, Cool

• = Standard ◦ = Optional

\*= Intensive-variant with 180 W tubes with long spot  
and 800 h recommended lifetime

| Type →                        | 50 XL              | 50 XL High Intensive* | 50 XL IP Control   | 50 XLc             | 50 XLc High Intensive* | 50 SLI                 | 50 SLI High Intensive*  |
|-------------------------------|--------------------|-----------------------|--------------------|--------------------|------------------------|------------------------|-------------------------|
| Tubes                         | 50 x 120 W         | 50 x 180 W            | 50 x IP Control    | 50 x 120 W         | 50 x 180 W             | 42 x 120 W<br>8 x 80 W | 42 x 180 W<br>8 x 140 W |
| Face tanner                   | -                  | -                     | -                  | Integrated         | Integrated             | 4 x 400 W              | 4 x 400 W               |
| SPS                           | -                  | -                     | -                  | -                  | -                      | •                      | •                       |
| HPS                           | -                  | -                     | -                  | -                  | -                      | ◦                      | ◦                       |
| Surface                       | Metallic           | Metallic              | Metallic           | Metallic           | Metallic               | Metallic               | Metallic                |
| Floor lighting                | •                  | •                     | •                  | •                  | •                      | •                      | •                       |
| DecoLight                     | •                  | •                     | •                  | •                  | •                      | •                      | •                       |
| Stand-by                      | •                  | •                     | •                  | •                  | •                      | •                      | •                       |
| inside lighting               | •                  | •                     | •                  | •                  | •                      | •                      | •                       |
| 2Doors open synchronous       | •                  | •                     | •                  | •                  | •                      | •                      | •                       |
| Digital timer display         | •                  | •                     | •                  | •                  | •                      | •                      | •                       |
| Internal timer                | •                  | •                     | •                  | •                  | •                      | •                      | •                       |
| Connection for external timer | •                  | •                     | •                  | •                  | •                      | •                      | •                       |
| Adjustable bodycooler: 1-2    | •                  | •                     | •                  | •                  | •                      | •                      | •                       |
| Lift system                   | ◦                  | ◦                     | ◦                  | ◦                  | ◦                      | ◦                      | ◦                       |
| Qsens (4 nozzles)             | ◦                  | ◦                     | ◦                  | ◦                  | ◦                      | ◦                      | ◦                       |
| Xsens                         | ◦                  | ◦                     | ◦                  | ◦                  | ◦                      | ◦                      | ◦                       |
| Loudspeakers                  | •                  | •                     | •                  | •                  | •                      | •                      | •                       |
| SoundAround                   | ◦                  | ◦                     | ◦                  | ◦                  | ◦                      | ◦                      | ◦                       |
| My MP3                        | ◦                  | ◦                     | ◦                  | ◦                  | ◦                      | ◦                      | ◦                       |
| SmartVoice                    | ◦                  | ◦                     | ◦                  | ◦                  | ◦                      | ◦                      | ◦                       |
| Hour-counter non-resetable    | •                  | •                     | •                  | •                  | •                      | •                      | •                       |
| Hour-counter resetable        | •                  | •                     | •                  | •                  | •                      | •                      | •                       |
| Connection                    | 400 V/3N ~/PE/50Hz | 400 V/3N ~/PE/50Hz    | 400 V/3N ~/PE/50Hz | 400 V/3N ~/PE/50Hz | 400 V/3N ~/PE/50Hz     | 400 V/3N ~/PE/50Hz     | 400 V/3N ~/PE/50Hz      |
| Power                         | 6,8kW              | 11,5kW                | 11,5kW             | 6,8kW              | 11,5kW                 | 8,5kW                  | 13kW                    |
| Fuses                         | 3 x 16 A           | 3 x 20 A              | 3 x 16 A           | 3 x 16 A           | 3 x 20 A               | 3 x 20 A               | 3 x 25 A                |
| Weight (excl. Packaging)      | 600 kg             | 650 kg                | 500 kg             | 600 kg             | 650 kg                 | 625 kg                 | 675 kg                  |