



## Technical data Luxura X<sub>7</sub>

### Available colors:

Mellow Lime  
Sunrise Orange  
Starlight Silver  
Eternal Blue  
Glamour Edition

\* = As standard ° = Optional

- On demand 42 SLi, 42 SLi Int., 42 SLi H. Int., 40 SPPr, 40 SPPr Int. en 40 SPPr H. Int. are available with 1,80 m tubes and
- Only available in combination with SoundAround
- CliMax only available in combination with ContourPlus
- Only available in combination with 1,80 m tubes in the base

Type ->	38 SLi	38 SLi Intensive	38 SLi High Intensive	40 SPPr	40 SPPr Intensive	40 SPPr High Intensive	42 SLi	42 SLi Intensive	42 SLi High Intensive	42 SLi IPControl
Surface	Metallic	Metallic	Metallic	Metallic	Metallic	Metallic	Metallic	Metallic	Metallic	Metallic
Inside lighting	•	•	•	•	•	•	•	•	•	•
Tubes top	22 x 100 W	22 x 160 W	22 x 160 W	22 x 120 W	22 x 180 W	22x 180 W	24 x 100 W	24 x 160 W	24 x 160 W	24 x IP lampen 1.80 m
Tubes base	16 x 100 W	16 x 100 W	16 x 160 W	18 x 120 W	18 x 120 W	18 x 180 W	18 x 120 W	18 x 120 W	18 x 180 W	18 x IP lampen 2.00 m
Face tanner	3 x 400 W	3 x 400 W	3 x 400 W	23 x 25 W	23 x 25 W	23 x 25 W	4 x 400 W	4 x 400 W	4 x 400 W	4 x 400 W
Luxura Filter technology	•	•	•	—	—	—	•	•	•	•
HPS	°	°	°	—	—	—	°	°	°	°
2 m tubes in base <sup>1</sup>	—	—	—	•	•	•	•	•	•	•
5 steps adjustable body cooler	•	•	•	•	•	•	•	•	•	•
5 steps adjustable face cooler	•	•	•	•	•	•	•	•	•	•
LED blower decor light	•	•	•	•	•	•	•	•	•	•
Decorative panel in colour of sunbed	•	•	•	•	•	•	•	•	•	•
Loudspeakers (2)	•	•	•	•	•	•	•	•	•	•
SoundAround including My MP3	°	°	°	°	°	°	•	•	•	•
SmartVoice <sup>2</sup>	°	°	°	°	°	°	°	°	°	°
ContourPlus	•	•	•	•	•	•	•	•	•	•
Xsens	°	°	°	°	°	°	°	°	°	°
Qsens	°	°	°	°	°	°	°	°	°	°
CliMax <sup>3</sup>	°	°	°	°	°	°	°	°	°	°
BackFlex	•	•	•	°4	°4	°4	°4	°4	°4	°4
Dust filters	•	•	•	•	•	•	•	•	•	•
EasyLift Acrylic system	•	•	•	•	•	•	•	•	•	•
Sound volume adjustment <sup>2</sup>	•	•	•	•	•	•	•	•	•	•
LCD timer display	•	•	•	•	•	•	•	•	•	•
Programmable internal timer	•	•	•	•	•	•	•	•	•	•
Connection for external timer	•	•	•	•	•	•	•	•	•	•
Hour counter	•	•	•	•	•	•	•	•	•	•
2nd hour counter with reset-function	•	•	•	•	•	•	•	•	•	•
Connection	400 V -50 Hz 3~N/PE	400 V -50 Hz 3~N/PE	400 V -50 Hz 3~N/PE	400 V -50 Hz 3~N/PE	400 V -50 Hz 3~N/PE	400 V -50 Hz 3~N/PE	400 V -50 Hz 3~N/PE	400 V -50 Hz 3~N/PE	400 V -50 Hz 3~N/PE	400 V -50 Hz 3~N/PE
Power (with CliMax)	ca. 6,3 (7,1) kW	ca. 7,6 (8,3) kW	ca. 9,3 (10,1) kW	ca. 5,9 (6,6) kW	ca. 7,4 (8,2) kW	ca. 8,5 (9,4) kW	ca. 7,2 (8,0) kW	ca. 9,0 (9,8) kW	ca. 10,2 (10,8) kW	ca. 9,4 (10,4) kW
Fuses	3 x 16 A	3 x 16 A	3 x 16 A	3 x 16 A	3 x 16 A	3 x 20 A	3 x 16 A	3 x 20 A	3 x 25 A	3 x 20 A
Weight (excl. packaging) (CliMax +50kg)	285 kg	305 kg	325 kg	295 kg	315 kg	330 kg	305 kg	325 kg	340 kg	285 kg